


STACKING S 60 V MLR VU - INDOOR

David Rockwell, 2025

LEUCOS



Discover more



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H60cm [Ø4" H23 5/8"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" H1 3/4"] Cable lenght: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 13,75W (total) 1581 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 13,75W (total) 1512 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	 
NET WEIGHT	3,2kg
ACCESSORIES	Round Cluster Canopy 55 Radial Cluster Canopy 33



[5]

 Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[5] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014500 0014502
[6] Trasparent Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014505 0014506
Amber Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014500/MA 0014502/MA
Amber Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014505/MA 0014506/MA

 Class 3 version installation with remote driver (supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[5] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014541 0014542
[6] Trasparent Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014545 0014546
Amber Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014541/MA 0014542/MA
Amber Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014545/MA 0014546/MA

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information