


STACKING S 60 V RIG VU - INDOOR

David Rockwell, 2025

LEUCOS



Discover more



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Rigadin Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H60cm [Ø4" H23 5/8"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" H1 3/4"] Cable lenght: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 13,75W (total) 1581 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 13,75W (total) 1512 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	 
NET WEIGHT	3,2kg
ACCESSORIES	Round Cluster Canopy 55 Radial Cluster Canopy 33



 Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[3] Trasparent Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0014507 0014508
[4] Trasparent Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0014511 0014512
Amber Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0014507/RA 0014508/RA
Amber Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0014511/RA 0014512/RA

 **Class 3 version installation with remote driver
(supplied without canopy & driver)**

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[3] Trasparent Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0014531 0014532
[4] Trasparent Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0014535 0014536
Amber Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0014531/RA 0014532/RA
Amber Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0014535/RA 0014536/RA