


STACKING S 90 V MLR - INDOOR

David Rockwell, 2024

LEUCOS



Discover more



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H90cm [Ø4" H35 3/8"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" H1 3/4"] Cable lenght: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 21,25W (total) 2443 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 21,25W (total) 2337 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	 
NET WEIGHT	5,4kg
ACCESSORIES	Round Cluster Canopy 55 Radial Cluster Canopy 33



 Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[5] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014610 0014611
[6] Trasparent Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014612 0014613
Amber Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014610/RA 0014611/RA
Amber Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014612/RA 0014613/RA

 **Class 3 version installation with remote driver
(supplied without canopy & driver)**

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[5] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014630 0014631
[6] Trasparent Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014632 0014633
Amber Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014630/RA 0014631/RA
Amber Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014632/RA 0014633/RA

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information