


STACKING S 30 V RIG - INDOOR

David Rockwell, 2024

LEUCOS



Discover more



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H30cm [Ø4" H11 3/4"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" H1 3/4"] Cable lenght: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	CE IP20
NET WEIGHT	2,7kg



Standard version (supplied with canopy & driver)		
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
Transparent Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0013557 0013558
Transparent Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0013882 0013883
Amber Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0013557/RA 0013558/RA
Amber Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0013882/RA 0013883/RA

Class 3 version installation with remote driver (supplied without canopy & driver)		
DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
Transparent Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0013559 0013560
Transparent Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0013820 0013821
Amber Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0013559/RA 0013560/RA
Amber Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0013820/RA 0013821/RA

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information