


STACKING P-PL 30 MLR

David Rockwell, 2025

LEUCOS



Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H32cm [Ø4" H12 5/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 6,25W total 718lm nominal 3000K CRI≥90 5XLED STRIP 24V 6,25W total 687lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; Dali
MARKING	 
NET WEIGHT	2 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014021 0014022
[2] Trasparent Millerighe + Matte Black	LED 3000K LED 2700K	0014061 0014060
Amber Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014021/MA 0014022/MA
Amber Millerighe + Matte Black Aluminum	LED 3000K LED 2700K	0014061/MA 0014060/MA