

STACKING P-PL 60 - INDOOR

David Rockwell, 2025



Discover more

REPLACEABLE LED

TECHNICAL SHEET	
TYPE	Wall/Ceiling
MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Anodized or painted aluminum
DIMENSIONS	Diffuser: [Ø4" H24 3/8"] Ø10cm H62cm Depth: [5 1/2"] 14cm
LIGHT SOURCE	5 X LED STRIP 24V 13,75W (total) 1581 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 13,75W (total) 1512 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION
NET WEIGHT	7 lbs
NOTE:	Can be installed vertically and horizontally

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

North America

LEUCOS



DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K LED 2700K	0014135 0014134		
Transparent + Matte Black Aluminum	LED 3000K LED 2700K	0014137 0014136		
**Metallic Petrol Blue + Anodized Aluminum	LED 3000K LED 2700K	0014256 0014257		
**Metallic Petrol Blue + Matte Black Aluminum	LED 3000K LED 2700K	0014258 0014259		
**Metallic Titanium + Anodized Aluminum	LED 3000K LED 2700K	0014260 0014261		
**Metallic Titanium + Matte Black Aluminum	LED 3000K LED 2700K	0014262 0014263		

****ON REQUEST:** PVD METALIZED TREATMENT
MINIMUM ORDER QUANTITY 4 PCS PER COLOR