


STACKING S 180 H MLR - INDOOR

David Rockwell, 2025



REPLACEABLE LED


TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [Ø4" 70 7/8"] Ø10cm L180cm Canopy: [15 3/4" x 2 3/4" x H1 5/8"] 40cm x 7cm x H4cm Cable lenght: [118 1/8"] 300cm
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 43,75W (total) 3830 lm (delivered) 3000K CRI≥90 5 X LED STRIP 43,75W (total) 3536 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V, Phase Cut
MARKING	DRY LOCATION 
NET WEIGHT	27 lbs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

North America

LEUCOS



100-277Vac 50-60Hz standard version
(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V, Phase Cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
[5] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014662 0014663		
[6] Trasparent Millerighe + Matte Black	LED 3000K LED 2700K	0014664 0014665		
Amber Millerighe + Anodized Aluminium	LED 3000K LED 2700K	0014662/MA 0014663/MA		
Amber Rigadin + Matte Black	LED 3000K LED 2700K	0014664/MA 0014665/MA		