


STACKING S 30 V - INDOOR

David Rockwell, 2023



Discover more



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [Ø4" H11 3/4"] Ø10cm H30cm Canopy: [Ø7 1/8" H1 7/8"] Ø18cm H4,9cm Cable lenght: [118 1/8"] 300cm
CANOPY	Matte White
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 541 lm (delivered) 3000K CRI≥90 5 X LED STRIP 6,25W (total) 530 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION 
NET WEIGHT	5,07 lbs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

North America

LEUCOS



100-277Vac 50-60Hz standard version
(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K LED 2700K	0012416 0012417		
Transparent + Matte Black Aluminum	LED 3000K LED 2700K	0013912 0013913		
**Metallic Petrol Blue + Anodized Aluminum	LED 3000K LED 2700K	0013756 0013757		
**Metallic Petrol Blue + Matte Black Aluminum	LED 3000K LED 2700K	0013760 0013761		
**Metallic Titanium + Anodized Aluminum	LED 3000K LED 2700K	0013764 0013765		
**Metallic Titanium + Matte Black Aluminum	LED 3000K LED 2700K	0013768 0013769		

**ON REQUEST: PVD METALIZED TREATMENT
MINIMUM ORDER QUANTITY 8 PCS PER COLOR