


STACKING S 30 V MLR VU - INDOOR

David Rockwell, 2025



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [Ø4" H11 3/4"] Ø10cm H30cm Canopy: [Ø5 3/4" H1 3/4"] Ø14,5cm H4,6cm Cable lenght: [118 1/8"] 300cm
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 541 lm (delivered) 3000K CRI≥90 5 X LED STRIP 6,25W (total) 530 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V, Phase Cut
MARKING	DRY LOCATION 
NET WEIGHT	6 lbs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

HQ: 6 Kilmer Rd Suite B - Edison, NJ 08817, US
WH: 2351 Us Highway 130 Ste B - Dayton, NJ 08810-1648, US

North America

LEUCOS



[5]

100-277Vac 50-60Hz standard version
(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V, Phase Cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
[5] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014525 0014526		
[6] Trasparent Millerighe + Matte Black	LED 3000K LED 2700K	0014529 0014530		
Amber Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014525/MA 0014526/MA		
Amber Millerighe + Matte Black	LED 3000K LED 2700K	0014529/MA 0014530/MA		

<https://www.leucos.com/en-us/info.us@leucos.com>

Tel +1 (732) 225-0010