


STACKING S 30 V - INDOOR

David Rockwell, 2023



Discover more

REPLACEABLE LED

North America

LEUCOS



100-277Vac 50-60Hz standard version

(supplied with canopy & driver)

DIMMING PROTOCOL		0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)		SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K	0012416			
	LED 2700K	0012417			

24Vdc version installation with remote driver

(supplied without canopy & driver)

DIMMING PROTOCOL		Driver and canopy not included			
FINISH (DIFFUSER + STRUCTURE)		SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K	0013281			
	LED 2700K	0013282			

TECHNICAL SHEET

MATERIALS Diffuser: Blown Borosilicate Glass
Structure: Aluminum

DIMENSIONS Diffuser: [04" H11 3/4"] Ø10cm H30cm
Canopy: [07 1/8" H1 7/8"] Ø18cm H4,9cm
Cable length: [118 1/8"] 300cm

CANOPY Matte White

LIGHT SOURCE 5 X LED STRIP 6,25W (total) 541 lm (delivered) 3000K CRI≥90
5 X LED STRIP 6,25W (total) 530 lm (delivered) 2700K CRI≥90

DIMMING PROTOCOL 0/1-10V; Phase cut

MARKING DRY LOCATION



WEIGHT Net weight: 5,07 Ibs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

11 Mayfield Avenue, Edison, NJ 08837 - USA
Tel +1 (732) 225-0010

<https://www.leucos.com/en-us/>
info.us@leucos.com