


**STACKING S 30 V - INDOOR**


David Rockwell, 2023

REPLACEABLE LED

North America

**LEUCOS**Discover  
more

## TECHNICAL SHEET

MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminium
DIMENSIONS	Diffuser: [Ø4" H11 3/4"] Ø10cm H30cm Canopy: [Ø5 3/4" 1 3/4"] Ø14,5cm H4,6cm Cable length: [118 1/8"] 300cm - feet 9.84'
FINISHES (DIFFUSER + STRUCTURE)	Transparent + Anodized Aluminium 
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 541 lm (delivered) 3000K CRI≥90 5 X LED STRIP 6,25W (total) 530 lm (delivered) 2700K CRI≥90
CONTROL	0/1-10V; Phase cut
MARKING	DRY LOCATION <span style="border: 1px solid black; padding: 2px;">IP20</span>
ON REQUEST	Customized end cups colors

Custom color



CONTROL	0/1-10V; Phase cut			
FINISH	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminium	LED 3000K LED 2700K	0012416 0012417		

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications. Please visit [www.leucos.com](http://www.leucos.com) for the latest product information