


STACKING S 30 V NAKED - INDOOR


David Rockwell, 2023



Discover more

REPLACEABLE LED

TECHNICAL SHEET

MATERIALS	Difuser: Polymethacrylate Structure: Aluminum
DIMENSIONS	Difuser: [$\varnothing 2\ 7/8''$ H $11\ 3/4''$] $\varnothing 7,5\text{cm}$ H 30cm Canopy: [$\varnothing 7\ 1/8''$ H $1\ 7/8''$] $\varnothing 18\text{cm}$ H $4,9\text{cm}$ Cable length: [$118\ 1/8''$] 300cm
CANOPY	Matte White
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 547 lm (delivered) 3000K CRI \geq 90 5 X LED STRIP 6,25W (total) 536 lm (delivered) 2700K CRI \geq 90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION 
WEIGHT	Net weight: 3,74 Ibs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information



100-277Vac 50-60Hz standard version

(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K	0012509		
	LED 2700K	0012510		

24Vdc version installation with remote driver

(supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K	0013391		
	LED 2700K	0013392		