


STACKING S 30 V RIG - INDOOR

David Rockwell, 2024



Discover more

REPLACEABLE LED

TECHNICAL SHEET

MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [Ø4" H11 3/4"] Ø10cm H30cm Canopy: [Ø7 1/8" H1 7/8"] Ø18cm H4,9cm Cable length: [118 1/8"] 300cm
CANOPY	Matte White
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 541 lm (delivered) 3000K CRI≥90 5 X LED STRIP 6,25W (total) 530 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION 
NET WEIGHT	5,60 Ibs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

North America

LEUCOS



100-277Vac 50-60Hz standard version

(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013587		
	LED 2700K	0013588		
Transparent Rigadin + Matte Black Aluminum	LED 3000K	0013922		
	LED 2700K	0013923		
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013812		
	LED 2700K	0013813		
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013816		
	LED 2700K	0013817		

24Vdc version installation with remote driver

(supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013589		
	LED 2700K	0013590		
Transparent Rigadin + Matte Black Aluminum	LED 3000K	0013820		
	LED 2700K	0013821		
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013814		
	LED 2700K	0013815		
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013818		
	LED 2700K	0013819		