


STACKING P-PL 30

David Rockwell, 2025

North America

LEUCOS



TECHNICAL SHEET	
MATERIALS	Diffuser: Smooth Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [Ø4" H12 5/8"] Ø10cm H32cm Depth: [5 1/2"] 14cm
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V, Phase Cut
MARKING	DRY LOCATION 
NET WEIGHT	4,2 lbs
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	0/1-10V, Phase Cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
[1] Trasparent + Anodized Aluminum	LED 3000K LED 2700K	0014033 0014034		
[2] Trasparent + Matte Black	LED 3000K LED 2700K	0014075 0014074		

ON REQUEST (PVD: METALIZED TREATMENT)

MINIMUM ORDER QUANTITY 8 PCS PER COLOR

DIMMING PROTOCOL	0/1-10V, Phase Cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
[3] Metallic Petrol Blue + Anodized Aluminum	LED 3000K LED 2700K	0014240 0014241		
[4] Metallic Petrol Blue + Matte Black	LED 3000K LED 2700K	0014242 0014243		
[5] Metallic Titanium + Anodized Aluminum	LED 3000K LED 2700K	0014244 0014245		
[6] Metallic Titanium + Matte Black	LED 3000K LED 2700K	0014246 0014247		

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information

HQ: 6 Kilmer Rd Suite B - Edison, NJ 08817, US
WH: 2351 Us Highway 130 Ste B - Dayton, NJ 08810-1648, US

<https://www.leucos.com/en-us/>
info.us@leucos.com

Tel +1 (732) 225-0010