


STACKING P-PL 30 MLR

David Rockwell, 2025

North America

LEUCOS



TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [Ø4" H12 5/8"] Ø10cm H32cm Depth: [5 1/2"] 14cm
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V, Phase Cut
MARKING	DRY LOCATION 
NET WEIGHT	4,4 lbs
NOTE	Can be installed vertically and horizontally

DIMMING PROTOCOL	0/1-10V, Phase Cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
[1] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014039 0014040		
[2] Trasparent Millerighe + Matte Black	LED 3000K LED 2700K	0014081 0014080		

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information