



Photometric Test Report


Appliance Dates & Address			
Applicant	LEUCOS	Address	Via del Commercio 22, 36060 Romano d'Ezzelino (VI)
Date of receipt of test item	6 luglio 2022	Model ref.	AURELIA 22 - DIRETTA
Technical datas	LED - 230V - 2700K		
Applied standard			
<input checked="" type="checkbox"/> UNI 13032-1:2012 + UNI 13032-4:2019		<input type="checkbox"/>	
Regional Law			
<input type="checkbox"/>		<input type="checkbox"/>	
Consideration / Notes:			
Environmental & Electrical Conditions:			
Operator	Gaetano Pagliaro	Temperature	25.00 °C
Rated Voltage		Humidity	60.00 %
Rated Current			
Luminaire Characteristics			
Round Luminaire Diam.	225 mm	Round Luminous Area Diam.	90 mm
Round Luminaire H.	240 mm	Round Luminous Area H.	0 mm
Summary of Results			
Coordinate system	CG	Symmetry Type	Asymmetrical
Measurement Distance	11.480 m	Maxi Gamma Angle	180
Luminaire Flux	978.58 lm	Sources Flux	978.58 lm
Luminaire Power	14.21 W	Maximum Value	390.06 cd/klm
Efficacy	68.87 lm/W	Position	C=0.00 G=0.00
Efficiency	100.00 %	CG Double Symmetrical	
Luminaire Lamps			
Manufacturer	LEUCOS	Flux (lm)	978.58
Model Ref.	AURELIA 22	Pow. (W)	14.21
		Q.t	1



ULOR 0.00%
DLOR 100.01%
RN 0.00%



Pictures of the tested sample:



UGR TABLE

S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Working Plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions	Viewed Crosswise					Viewed Endwise				
X=2H y=2H	26.0	27.3	26.3	27.5	27.7	25.8	27.0	26.1	27.2	27.5
X=2H y=3H	27.3	28.4	27.6	28.6	28.9	27.0	28.1	27.3	28.4	28.6
X=2H y=4H	27.7	28.7	28.0	29.0	29.3	27.4	28.5	27.7	28.7	29.0
X=2H y=6H	27.9	28.9	28.3	29.2	29.5	27.6	28.6	28.0	28.9	29.2
X=2H y=8H	28.0	28.9	28.3	29.2	29.5	27.7	28.6	28.0	28.9	29.3
X=2H y=12H	27.9	28.8	28.3	29.1	29.5	27.6	28.5	28.0	28.9	29.2
X=4H y=2H	26.6	27.7	27.0	28.0	28.3	26.4	27.4	26.7	27.7	28.0
X=4H y=3H	28.0	28.9	28.4	29.2	29.6	27.7	28.6	28.1	29.0	29.3
X=4H y=4H	28.6	29.3	28.9	29.7	30.1	28.3	29.1	28.7	29.4	29.8
X=4H y=6H	28.9	29.6	29.3	29.9	30.3	28.6	29.3	29.0	29.7	30.1
X=4H y=8H	29.0	29.6	29.4	30.0	30.4	28.7	29.3	29.1	29.7	30.1
X=4H y=12H	28.9	29.5	29.4	29.9	30.4	28.6	29.2	29.1	29.6	30.0
X=8H y=4H	28.8	29.4	29.2	29.8	30.2	28.5	29.1	28.9	29.5	29.9
X=8H y=6H	29.2	29.7	29.6	30.1	30.6	28.9	29.4	29.3	29.8	30.3
X=8H y=8H	29.3	29.7	29.7	30.2	30.6	29.0	29.4	29.4	29.9	30.3
X=8H y=12H	29.3	29.6	29.8	30.1	30.6	28.9	29.3	29.4	29.8	30.3
X=12H y=4H	28.8	29.3	29.2	29.7	30.2	28.5	29.1	28.9	29.5	29.9
X=12H y=6H	29.2	29.6	29.7	30.1	30.6	28.9	29.3	29.4	29.8	30.3
X=12H y=8H	29.3	29.7	29.8	30.1	30.6	29.0	29.3	29.5	29.8	30.3

Testing Laboratory: Zanelli S.r.l.
Tested by Gaetano Pagliaro

FIRMA:
Gaetano Pagliaro