


STACKING S 30 V NAKED - INDOOR

David Rockwell, 2023



LEUCOS



Discover more

REPLACEABLE LED



TECHNICAL SHEET	
MATERIALS	Diffuser: Polymethacrylate Structure: Aluminum
DIMENSIONS	Diffuser: Ø7,5cm H30cm [Ø2 7/8" H11 3/4"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" 1 3/4"] Cable lenght: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	DRY LOCATION  
WEIGHT	Net weight: 1,7kg

Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
White + Anodized Aluminum	LED 3000K	0012439
	LED 2700K	0012440

Class 3 version installation with remote driver (supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
White + Anodized Aluminum	LED 3000K	0013267
	LED 2700K	0013268

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information