


STACKING S 60 V RIG - INDOOR

David Rockwell, 2024

LEUCOS



Discover more

REPLACEABLE LED

TECHNICAL SHEET

MATERIALS Diffuser: Blown Borosilicate Glass
Structure: Aluminum

DIMENSIONS Diffuser: Ø10cm H60cm [Ø4" 23 5/8"]
Canopy: Ø14,5cm H4,6cm [Ø5 3/4" 1 3/4"]
Cable lenght: 300cm [118 1/8"]

CANOPY Matte white

LIGHT SOURCE 5 X LED STRIP 24V 13,75W (total) 1581 lm (nominal) 3000K CRI≥90
5 X LED STRIP 24V 13,75W (total) 1512 lm (nominal) 2700K CRI≥90

DIMMING PROTOCOL Push-dim; 0/1-10V, DALI

MARKING  

NET WEIGHT 3,5 kg



Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013553
	LED 2700K	0013554

Class 3 version installation with remote driver (supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013555
	LED 2700K	0013556

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information