


STACKING P-PL 30

David Rockwell, 2025

LEUCOS



Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Smooth Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H32cm [Ø4" 12 5/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 6,25W total 718lm nominal 3000K CRI≥90 5XLED STRIP 24V 6,25W total 687lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; Dali
MARKING	  IP20
NET WEIGHT	1,9 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL		Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)		SOURCE	CODE
[1]	Trasparent + Anodized Aluminum	LED 3000K LED 2700K	0014013 0014015
[2]	Trasparent + Matte Black	LED 3000K LED 2700K	0014055 0014054

ON REQUEST (PVD: METALIZED TREATMENT)

MINIMUM ORDER QUANTITY 8 PCS PER COLOR

DIMMING PROTOCOL		Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)		SOURCE	CODE
[3]	Metallic Petrol Blue + Anodized Aluminum	LED 3000K LED 2700K	0014174 0014175
[4]	Metallic Petrol Blue + Matte Black	LED 3000K LED 2700K	0014176 0014177
[5]	Metallic Titanium + Anodized Aluminum	LED 3000K LED 2700K	0014178 0014179
[6]	Metallic Titanium + Matte Black	LED 3000K LED 2700K	0014180 0014181

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information