




Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Smooth Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H62cm [Ø4" H24 3/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 13,75W total 1581lm nominal 3000K CRI≥90 5XLED STRIP 24V 13,75W total 1512lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; DALI
MARKING	 
NET WEIGHT	3 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent + Anodized Alu	LED 3000K LED 2700K	0014095 0014094
[2] Trasparent + Matte Black	LED 3000K LED 2700K	0014096 0014097

ON REQUEST (PVD: METALIZED TREATMENT)

MINIMUM ORDER QUANTITY 4 PCS PER COLOR

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[3] Metallic Petrol Blue + Anodized Aluminum	LED 3000K LED 2700K	0014190 0014191
[4] Metallic Petrol Blue + Matte Black	LED 3000K LED 2700K	0014192 0014193
[5] Metallic Titanium + Anodized Aluminum	LED 3000K LED 2700K	0014194 0014195
[6] Metallic Titanium + Matte Black	LED 3000K LED 2700K	0014196 0014197


STACKING P-PL 60 RIG

David Rockwell, 2025

LEUCOS



Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Rigadin Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H62cm [Ø4" H24 2/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 13,75W total 1581lm nominal 3000K CRI≥90 5XLED STRIP 24V 13,75W total 1512lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; Dali
MARKING	  IP20
NET WEIGHT	3,5 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent Rigadin + Anodized Alu	LED 3000K LED 2700K	0014099 0014098
[2] Trasparent Rigadin + Matte Black	LED 3000K LED 2700K	0014101 0014100

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information


STACKING P-PL 60 RIG VU

David Rockwell, 2025

LEUCOS



Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Rigadin Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H62cm [Ø4" H24 2/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 13,75W total 1581lm nominal 3000K CRI≥90 5XLED STRIP 24V 13,75W total 1512lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; Dali
MARKING	  IP20
NET WEIGHT	3,5 Kg
NOTE	Can be installed vertically and horizontally



[1]

DIMMING PROTOCOL	Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent Rigadin + Anodized Alu	LED 3000K LED 2700K	0014103 0014102
[2] Trasparent Rigadin + Matte Black	LED 3000K LED 2700K	0014105 0014104

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information


STACKING P-PL 60 MLR

David Rockwell, 2025

LEUCOS



Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H62cm [Ø4" H24 2/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 13,75W total 1581lm nominal 3000K CRI≥90 5XLED STRIP 24V 13,75W total 1512lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	  IP20
NET WEIGHT	3,1 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent Millerighe + Anodized Alu	LED 3000K LED 2700K	0014107 0014106
[2] Trasparent Millerighe + Matte Black	LED 3000K LED 2700K	0014109 0014108

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information


STACKING P-PL 60 MLR VU

David Rockwell, 2025

LEUCOS



Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Millerighe Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H62cm [Ø4" H24 2/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 13,75W total 1581lm nominal 3000K CRI≥90 5XLED STRIP 24V 13,75W total 1512lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; Dali
MARKING	  IP20
NET WEIGHT	3,1 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	Push-dim; Dali	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent Millerighe + Anodized Aluminum	LED 3000K LED 2700K	0014111 0014110
[2] Trasparent Millerighe + Matte Black	LED 3000K LED 2700K	0014113 0014112

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information