




Discover more



TECHNICAL SHEET	
MATERIALS	Diffuser: Smooth Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H62cm [Ø4" H24 3/8"] Depth: 14cm [5 1/2"]
LIGHT SOURCE	5XLED STRIP 24V 13,75W total 1581lm nominal 3000K CRI≥90 5XLED STRIP 24V 13,75W total 1512lm nominal 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; DALI
MARKING	  IP20
NET WEIGHT	3 Kg
NOTE	Can be installed vertically and horizontally



DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[1] Trasparent + Anodized Aluminum	LED 3000K LED 2700K	0014095 0014094
[2] Trasparent + Matte Black	LED 3000K LED 2700K	0014096 0014097

ON REQUEST (PVD: METALIZED TREATMENT)

MINIMUM ORDER QUANTITY 4 PCS PER COLOR

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[3] Metallic Petrol Blue + Anodized Aluminum	LED 3000K LED 2700K	0014190 0014191
[4] Metallic Petrol Blue + Matte Black	LED 3000K LED 2700K	0014192 0014193
[5] Metallic Titanium + Anodized Aluminum	LED 3000K LED 2700K	0014194 0014195
[6] Metallic Titanium + Matte Black	LED 3000K LED 2700K	0014196 0014197