


STACKING S 30 V RIG VU - INDOOR

David Rockwell, 2025

LEUCOS



REPLACEABLE LED

TECHNICAL SHEET	
MATERIALS	Diffuser: Rigadin Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: Ø10cm H30cm [Ø4" H11 3/4"] Canopy: Ø14,5cm H4,6cm [Ø5 3/4" H1 3/4"] Cable lenght: 300cm [118 1/8"]
CANOPY	Matte white
LIGHT SOURCE	5 X LED STRIP 24V 6,25W (total) 718 lm (nominal) 3000K CRI≥90 5 X LED STRIP 24V 6,25W (total) 687 lm (nominal) 2700K CRI≥90
DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI
MARKING	CE IP 20
NET WEIGHT	2,7kg
ACCESSORIES	Round Cluster Canopy 55 Radial Cluster Canopy 33



Standard version (supplied with canopy & driver)

DIMMING PROTOCOL	Push-dim; 0/1-10V, DALI	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[3] Trasparent Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0014507 0014508
[4] Trasparent Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0014511 0014512

Class 3 version installation with remote driver (supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included	
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE
[3] Trasparent Rigadin + Anodized Aluminum	LED 3000K LED 2700K	0014531 0014532
[4] Trasparent Rigadin + Matte Black Aluminum	LED 3000K LED 2700K	0014535 0014536

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information