


STACKING S 60 V RIG VU - INDOOR

David Rockwell, 2025

LEUCOS



Discover more



REPLACEABLE LED

| TECHNICAL SHEET  |                                                                                                                                    |
|------------------|------------------------------------------------------------------------------------------------------------------------------------|
| MATERIALS        | Diffuser: Rigadin Borosilicate Glass<br>Structure: Aluminum                                                                        |
| DIMENSIONS       | Diffuser: Ø10cm H60cm [Ø4" 23 5/8"]<br>Canopy: Ø14,5cm H4,6cm [Ø5 3/4" 1 3/4"]<br>Cable lenght: 300cm [118 1/8"]                   |
| CANOPY           | Matte white                                                                                                                        |
| LIGHT SOURCE     | 5 X LED STRIP 24V 13,75W (total) 1581 lm (nominal) 3000K CRI≥90<br>5 X LED STRIP 24V 13,75W (total) 1512 lm (nominal) 2700K CRI≥90 |
| DIMMING PROTOCOL | Push-dim; 0/1-10V, DALI                                                                                                            |
| MARKING          | CE IP 20                                                                                                                           |
| NET WEIGHT       | 3,2kg                                                                                                                              |
| ACCESSORIES      | Round Cluster Canopy 55<br>Radial Cluster Canopy 33                                                                                |



Standard version (supplied with canopy & driver)

| DIMMING PROTOCOL                              | Push-dim; 0/1-10V, DALI |                    |
|-----------------------------------------------|-------------------------|--------------------|
| FINISH (DIFFUSER + STRUCTURE)                 | SOURCE                  | CODE               |
| [3] Trasparent Rigadin + Anodized Aluminum    | LED 3000K<br>LED 2700K  | 0014499<br>0014501 |
| [4] Trasparent Rigadin + Matte Black Aluminum | LED 3000K<br>LED 2700K  | 0014503<br>0014504 |

Class 3 version installation with remote driver (supplied without canopy & driver)

| DIMMING PROTOCOL                              | Driver and canopy not included |                    |
|-----------------------------------------------|--------------------------------|--------------------|
| FINISH (DIFFUSER + STRUCTURE)                 | SOURCE                         | CODE               |
| [3] Trasparent Rigadin + Anodized Aluminum    | LED 3000K<br>LED 2700K         | 0014539<br>0014540 |
| [4] Trasparent Rigadin + Matte Black Aluminum | LED 3000K<br>LED 2700K         | 0014543<br>0014544 |

We reserve the right to change our product specifications.  
Please visit [www.leucos.com](http://www.leucos.com) for the latest product information